06/09/2024 65511

WOLF RACING ESTER 10W-60 FS

This sustainable RRBO racing oil is fortified with ester, PAO, and a precisely balanced component-blended additive system delivering high levels of anti-wear and friction reducing characteristics. This advanced protection is engineered to help deliver optimum horsepower.

APPLICATIONS

This sustainable advanced racing oil is specifically designed for racing engines. Its high performance is designed to offer excellent friction reduction.

FEATURES

Total engine protection: performance in keeping the engine clean. Driving style: sporty driving.

SPECIFICATIONS

API	SN	FORD	RALLY CARS
BMW	M-SERIES	IRMSCHER	7
DONKERVOORT	COSWORTH	PORSCHE	VINTAGE CARS

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.862
Kinematic viscosity at 40°C	ASTM D445	mm²/s	154.1
Kinematic viscosity at 100°C	ASTM D445	mm²/s	23.1
Viscosity index	ASTM D2270		180
Pour point	ASTM D6892	°C	-48
Colour	VISUAL		DARK GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV G. Gilliotstraat 52 – 2620 Hemiksem – Belgium Tel. +32 (0)3 870 00 00 www.wolflubes.com

