

WOLF RACING TRANS 75W-140 ESTER

26/03/2024
65520

This is a full synthetic Extreme Pressure high performance gearbox and transaxle lubricant, enriched with ester, for racing vehicles offering an excellent anti-wear protection, a better resistance at high temperatures and a longer oil life time. It is blue colored.

APPLICATIONS

This lubricant can be used in gearboxes, transaxles and differentials with or without limited slip of racing vehicles.

FEATURES

Anti-wear protection: extended component life.
Extended oil life: excellent thermal and oxidation stability.

SPECIFICATIONS

API	GL-5	ZF	TE-ML 05C
API	GL-6	ZF	TE-ML 07A
API	MT-1	ZF	TE-ML 12D
MIL	L-2105 B	ZF	TE-ML 12N
MIL	L-2105 C	ZF	TE-ML 16F
MIL	L-2105 D	ZF	TE-ML 16G
MIL	L-2105 E	ZF	TE-ML 18
SAE	J 2360	ZF	TE-ML 19C
ARVIN MERITOR	0-76-M	ZF	TE-ML 21A
BMW	83 22 9 407 803	ZF	TE-ML 21C
BMW	83 22 9 407 870	ZF	TE-ML 21D
BMW	83221470080		
BMW	83222282583		
BMW	MSP/A		
CHRYSLER	68218658AA		
CHRYSLER	MS 8985		
DREXLER	.		
FERRARI	PAKELO GLOBAL MULTIGEAR DLS		
FORD	WSS-M2C187-A		
FORD	WSS-M2C192A+/M2C118-A		
GM	12346140		
GM	1942386		
GM	9986226		
MACK	GO-J		
MB	235.61		
NISSAN	2189E		
SCANIA	STO 1:0		
SCANIA	STO 2:0A		
VW	G 052 539		
ZF	TE-ML 05A		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.898
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	174
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	24.5
Viscosity index	ASTM D2270		173
Pour point	ASTM D6892	°C	-51
Colour	VISUAL		BLUE

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

