

WOLF OFFICIALTECH OW-20 C5 P

31/05/2024
65657

A low SAPS ACEA C5 passenger car engine oil focused on the most recent Stellantis / PSA specification B71 2010, but also suitable for diesel and gasoline engines from other car manufacturers which require an ACEA C5 SAE OW-20 oil.

APPLICATIONS

Specifically designed for the most recent PSA GROUP (Peugeot/Citroën/DS) engines which require a PSA B71 2010 oil as Blue HDi, PureTech, hybrid engines, engines equipped with a Stop & Start system, etc. This ACEA C5 oil is also suitable for diesel and gasoline engines from other car manufacturers which require an ACEA C5 SAE OW-20 oil.

FEATURES

Aftertreatment protection: full aftertreatment device protection.

Cold start: excellent fluidity at low temperature.

Fuel economy: superior fuel economy and CO2 reduction.

SPECIFICATIONS

ACEA	C5
API	SP
ILSAC	GF-5
ILSAC	GF-6 A
CHRYSLER	MS 6395
FIAT	9.55535-CR1
FIAT	9.55535-DM1
FIAT	9.55535-DSX
FIAT	9.55535-GSX
HONDA	.
HYUNDAI	.
INFINITI	.
KIA	.
LEXUS	.
MAZDA	.
MITSUBISHI	.
NISSAN	.
OPEL	OV 040 1547 - A20
PERODUA	.
PSA	approval B71 2010-22
ROEWE	.
SCION	.
SUBARU	.
SUZUKI	.
TATA	.
TIANJIN	.
TOYOTA	.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.845
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	43.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.3
Viscosity index	ASTM D2270		170
Pour point	ASTM D6892	°C	-48
Flash Point COC	ASTM D92	°C	232

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

