

WOLF OE LEVELTECH 5W30 LL III

29/04/2024
75602

This full synthetic engine oil is formulated to meet the specifications of different OEMs. It reaches ACEA and API requirements by balancing excellent fluidity with advanced engine protecting, regardless the driving conditions. This product may not be available in your region. Please, consult your local sales contact for more information.

APPLICATIONS

Its formulation is designed to meet the VW 504.00 and 507.00 specifications. This engine oil can be used to service a range of different EURO 4 and EURO 5-engines equipped with diesel particulate filters.

FEATURES

Aftertreatment protection:: full aftertreatment device protection.

Total engine protection:: outstanding engine cleanliness and durability.

SPECIFICATIONS

| | | | |
|------|-------------|---------|---------------|
| ACEA | C2 | MB | 229.51 |
| ACEA | C3 | MB | 229.52 |
| API | CF | PORSCHE | C30 |
| BMW | LONGLIFE-04 | VW | 504 00/507 00 |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.856 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 68.0 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 11.7 |
| Viscosity index | ASTM D2270 | | 169 |
| B.N. (HClO4 method) | ASTM D2896 | mg KOH/g | 8.3 |
| Pour point | ASTM D6892 | °C | -39 |
| Sulfated Ash | ASTM D874 | Mass % | 0.7 |
| Flash Point COC | ASTM D92 | °C | 230 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

