

WOLF ANH CA GREASE EP 00

09/07/2024
9280

This lithium-free multipurpose grease is an anhydrous calcium (ANH Ca) thickened lubricating grease based on a mineral oil.

The grease contains antioxidants, corrosion inhibitors and EP/AW additives.

APPLICATIONS

The ANH Ca thickener, together with the special base oil blend, makes this grease suitable for the lubrication of medium loaded bearings and in wet and corrosive environments.

This lubricating grease has excellent adhesion and water resistance.

The NLGI 00 consistency of the product makes it suitable for use in centralised lubrication systems that require semi-fluid grease. Also suitable for use in gearboxes.

FEATURES

Corrosion protection: very good corrosion protection.

Multi-applicability: wide range of use.

Water resistance: very good water resistance.

SPECIFICATIONS

| | | | |
|-----|-------|-----|--------------|
| DIN | 51502 | DIN | KP00M-40 |
| ISO | 12924 | ISO | L-XD(F)CIB00 |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|---------------------------------|---------------------------|--------|-----------------|
| Texture | Visual | | SMOOTH |
| Colour | VISUAL | | Yellow Brown |
| NLGI Classification | ASTM D217 | | 00 |
| Worked Penetration (60 strokes) | ISO 2137 | 0.1 mm | 400-430 |
| Dropping point | ISO 2176/IP 396 | °C | > 140 |
| Four Ball Weld Load | ASTM D2596/ DIN51350:4 | N | 3000 |
| Base Oil Viscosity at 40 °C | ASTM D7152 | cSt | 220 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

