

WOLF VITALTECH 20W50

02/09/2024
14647

This is a high-performance mineral diesel engine oil formulated to deliver reliable performance in a broad range of heavy-duty applications. It is suitable for low-emission engines (Euro II, Euro III and some Euro IV engines).

APPLICATIONS

Recommended for all modern diesel engines of trucks, off-road equipment and other heavy-duty applications. Universal use, including mixed fleets. Suitable for low-emission diesel engines with EGR (Euro II, III and some Euro IV). Meets and exceeds the demanding requirements of many U.S. and European diesel engine manufacturers.

FEATURES

Total engine protection: outstanding engine cleanliness and durability.
Cold start: very good fluidity at low temperature.

SPECIFICATIONS

ACEA	A3/B4	RENAULT	RLD
ACEA	E7	RENAULT	RLD-2
API	approval CI-4/SL	VOLVO	VDS-3
API	CF-4		
API	CG-4		
API	CH-4		
JASO	DH-1		
CATERPILLAR	ECF-1a		
CATERPILLAR	ECF-2		
CATERPILLAR	TO-2		
CUMMINS	CES 20076		
CUMMINS	CES 20077		
CUMMINS	CES 20078		
DAIMLER TRUCK	DTFR 15B110		
DETROIT DIESEL	DFS 93K215		
DEUTZ	DQC-III-10		
DEUTZ	DQC-III-18		
GLOBAL	DHD-1		
IVECO	18-1804 Classe T2 E7		
MACK	EO-L		
MACK	EO-M PLUS		
MACK	EO-N		
MAN	M3275-1		
MB	228.3		
MB	229.1		
MTU	Oil Category 1		
MTU	Oil Category 2		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.892
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	177
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	18.0
Viscosity index	ASTM D2270		112
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	10.7
Pour point	ASTM D6892	°C	-30
Sulfated Ash	ASTM D874	Mass %	1.34
Flash Point COC	ASTM D92	°C	232

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

