

WOLF OFFICIALTECH 10W40 UHPD

22/01/2026
15726

This is a synthetic lubricant based on carefully selected very high quality base oils, which satisfies the highest performance standards for large trucks. It can be used for engines equipped with after treatment systems, in combination with low-sulfur diesel (maximum 50 ppm).

APPLICATIONS

Due to its versatile specification levels it is suitable for a wide range of commercial vehicles. Specifically recommended for large truck engines to satisfy the EURO V-standard and suitable for most Euro VI engines. Perfectly compatible with all after treatment systems and devices (EGR, SCR, DPF, etc.) in combination with low sulfur diesel (max 50 ppm). Can also be used in older diesel engines (Euro II, III, IV). Also suitable for some gas-powered engines (CNG).

FEATURES

Aftertreatment protection: full after treatment system protection
Total engine protection: outstanding engine cleanliness and durability

SPECIFICATIONS

| | | | |
|----------------|-----------------------|-------|-------|
| ACEA | E4 | VOLVO | VDS-3 |
| ACEA | E6 | VOLVO | VDS-4 |
| ACEA | E7 | | |
| ACEA | E9 | | |
| API | CJ-4/SN | | |
| JASO | DH-1 | | |
| JASO | DH-2 | | |
| CATERPILLAR | ECF-3 | | |
| CUMMINS | CES 20081 | | |
| DAF | EXTENDED DRAIN | | |
| DETROIT DIESEL | DFS 93K218 | | |
| DEUTZ | DQC IV-10 LA | | |
| DTRF | 15C110 | | |
| IVECO | 18-1804 Classe TLS E9 | | |
| JD | JDQ-78X | | |
| MACK | EO-N Premium Plus | | |
| MACK | EO-O Premium Plus | | |
| MAN | M3271-1 | | |
| MAN | M3477 | | |
| MAN | M3575 | | |
| MTU | Oil Category 2.1 | | |
| MTU | Oil Category 3.1 | | |
| RENAULT | RLD-2 | | |
| RENAULT | RLD-3 | | |
| SCANIA | LA | | |
| VOITH | Retarder Oil Class B | | |

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.864 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 88.2 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 13.8 |
| Viscosity index | ASTM D2270 | | 157 |
| B.N. (HClO4 method) | ASTM D2896 | mg KOH/g | 12.8 |
| Pour point | ASTM D6892 | °C | -33 |
| CCS viscosity at -25°C | ASTM D5293 | mPa.s | 6200 |
| Sulfated Ash | ASTM D874 | Mass % | 0.98 |
| Flash Point COC | ASTM D92 | °C | 226 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

