

WOLF GUARDTECH 80W90 GL 1&3

11/08/2023
2108

This is a lubricant for gearboxes and rear axles with conical teeth or screw type. This oil is made with highly refined base oils containing anti-wear additives and an additive to lower the pour point.

APPLICATIONS

It can be used in manual gearboxes and rear axles where oils of API GL level 1&3 are prescribed, eg. in most FIAT-IVECO or VOLVO trucks and also in Fuller gearboxes.

FEATURES

Anti-wear protection: long transmission life

PERFORMANCE

API	GL-1	VOLVO	97305
API	GL-3		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.889
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	115.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14.7
Viscosity index	ASTM D2270		131
Pour point	ASTM D6892	°C	-33
Brookfield viscosity at -26 C	ASTM D2983	mPa.s	130000
Flash Point COC	ASTM D92	°C	212

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

