

WOLF VITALTECH 75W-80 MV PREMIUM

30/10/2024
2219

This is a high quality semi synthetic transmission oil, suitable for nearly all manual gearboxes of passenger cars. It is especially suitable as a replacement for specific OEM original oils and reduces the complexity and storage of gearbox oils. Tested under strict conditions, this oil satisfies the general performance requirements of most car makers and models.

APPLICATIONS

This oil is recommended for all hypoid transmissions and is also suitable for spiral bevel gears, worm wheels and most transaxles in all weather.

FEATURES

Frictional properties: very smooth gear shifting, no vibration.

Anti-wear protection: significantly extended transmission life.

Extended oil life: proven resistance to oil degradation.

SPECIFICATIONS

API	GL-4 +	VW	G 052 527
BMW	83 22 0 140 516	VW	G 052 532
BMW	83220309031	VW	G 052 726
BMW	MTF LT-2	VW	G 055 538
FIAT	9.55550-MX3		
FIAT	9.55550-MZ1		
FIAT	9.55550-MZ10		
FORD	ESD-M2C186-A		
FORD	WSS-M2C200-D2		
GM	1940182		
GM	1940768		
GM	93165290		
HONDA	MTF 94		
HYUNDAI	02200-00130 TOD		
LAND ROVER	TYK500030		
MB	235.10		
MITSUBISHI	MZ312644		
NISSAN	999MP-MTF20P		
NISSAN	MT-XZ		
PSA	9730 A2		
PSA	9730 A8		
PSA	B71 2330		
SUBARU	K0321-F0090		
TOYOTA	JWS 227		
VOLVO	97308		
VOLVO	97309		
VOLVO	97310		
VW	G 052 171		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.867
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	48.2
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.8
Viscosity index	ASTM D2270		164
Pour point	ASTM D6892	°C	-39
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	100000
Flash Point COC	ASTM D92	°C	212

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

