

# WOLF GUARDTECH 10W40 B4 DIESEL

11/08/2023  
23126

This is a semi synthetic lubricant based on carefully selected highly refined base oils. It is designed for the lubrication of four-stroke diesel cars, including diesel engines with direct injection such as Common Rail, HDI, CDI, etc. The use of high-quality components ensures that the oil has a great fluidity at low temperature and a stable viscosity at high temperatures. Its low ash formulation is combined with a high resistance to ageing.

## APPLICATIONS

This oil is used for most diesel engines, both normally aspirated and supercharged. It is particularly recommended for direct-injection diesel engines. Because of its excellent viscosity index it can be used all year round.

## FEATURES

Total engine protection: performance in keeping the engine clean  
Cold start: very good fluidity at low temperature

## PERFORMANCE

ACEA	A3/B3	MB	229.1
ACEA	A3/B4	VW	501 01
API	SL/CF	VW	505 00

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.865
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	91
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	13.7
Viscosity index	ASTM D2270		153
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-39
CCS viscosity at -25°C	ASTM D5293	mPa.s	6700
Sulfated Ash	ASTM D874	Mass %	1.0
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfubes.com](http://www.wolfubes.com)

