

WOLF OFFICIALTECH

75W-85 FE LS GL 5

13/11/2024
2318

This premium, fully synthetic, transmission SAE 75W-85 limited slip (LS) oil is especially developed for manual transmissions and differentials (LS and non-LS). The use of special friction modifiers reduces internal friction, thereby obtaining fuel economy (FE) properties.

APPLICATIONS

This fuel-saving, fully synthetic SAE 75W-85 transmission oil with Limited Slip properties has been specifically engineered for use in Mercedes Benz passenger car axles and other applications specified by MB 235.7, MB 235.74, MB 239.71 or MB 239.72.

Amongst many other applications also suitable for VAG Multitronic transmissions for which VW's TL 521 90 specification is required.

FEATURES

Low viscosity: fuel economy potential.

Frictional properties: easy gear shifting.

Excellent thermal stability: long gear and bearing life.

SPECIFICATIONS

API	GL-4	CHRYSLER	68232948AA
API	GL-5	CHRYSLER	68237820AA
API	MT-1	CHRYSLER	68333589AA
MIL	L-2105 D	CHRYSLER	68378949AA
MIL	L-2105 E	CHRYSLER	ELSD REAR AXLE
SAE	J 2360	CHRYSLER	MS A0450
ACURA	08200-9014A	DODGE	SFU
ACURA	HYPOID GEAR OIL HGO-1	FIAT	9.55550,CTR F426.E06
AISIN-WARNER	JWS 2273	FIAT	9.55550-DA3
BMW	83 12 0 445 838	FIAT	9.55550-DA8
BMW	83 22 2 239 982	FIAT	9.55550-DA9
BMW	83 22 2 295 532	FIAT	9.55550-MX3
BMW	83 22 2 413 511	FIAT	9.55550-MZ3
BMW	83 22 2 413 512	FORD	WSS-M2C942-A
BMW	83 22 2 447 362	FORD	XY-75W85-QL
BMW	BOT 448	GENESIS	SFU
BMW	HYPOID AXLE OIL G1	GM	19300457
BMW	HYPOID AXLE OIL G2	GM	1940012
BMW	HYPOID AXLE OIL G3	GM	19418501
BMW	HYPOID AXLE OIL G4	GM	1942067
CADILLAC	SFU	GM	88862826
CHRYSLER	05136035AA	GM	92184900
CHRYSLER	68083381AA	GM	93165290
CHRYSLER	68210057AA	GM	9986551
CHRYSLER	68218654AA	GM	SAF CARBON MOD

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



GM	SAF-EH MOD LV	MB	A 001 989 59 03
GMC	SFU	MB	A 002 989 02 03
HONDA	08200-9014	MG	SFU
INFINITI	KDL38-75801P	MOPAR	LL HYPOID GEAR OIL
JAGUAR	SFU	NISSAN	KDL38-75801P
JEEP	SFU	TOYOTA	08885-02506
LAND ROVER	LR052059	TOYOTA	08885-02606
LEXUS	08885-02506	TOYOTA	08885-81060
LEXUS	08885-02606	TOYOTA	08885-81070
LEXUS	08885-81060	TOYOTA	08885-81081
LEXUS	GEAR OIL LT/LX	TOYOTA	GEAR OIL LT/LX
LINCOLN	SFU	TOYOTA	JWS 2273
MAZDA	HYPOID GEAR OIL (SG1)	VOLVO	97312
MAZDA	K020-01-SG1	VW	G 052 145
MB	231.1	VW	G 052 190
MB	235.15	VW	G 052 196
MB	235.31	VW	G 052 513
MB	235.62	VW	G 055 190
MB	235.7	VW	G 060 190
MB	235.74	VW	TL 52 190
MB	239.71	ZF	TE-ML 02B
MB	239.72	ZF	TE-ML 08
MB	A 000 989 73 04	ZF	TE-ML 12F
MB	A 000 989 88 03	ZF	TE-ML 18
MB	A 001 989 33 03	ZF	TE-ML 19D

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.863
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	53.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.4
Viscosity index	ASTM D2270		215
Pour point	ASTM D6892	°C	-45
Flash Point COC	ASTM D92	°C	200

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

