

WOLF VITALTECH MULTI VEHICLE ATF

20/01/2026
3010

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions, meeting the requirements of most American, Japanese and European manufacturers.

APPLICATIONS

Its versatile nature guarantees it can be used in automatic transmissions and torque converters for most passenger cars, off-road vehicles and SUVs.

FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: significantly extended transmission life
Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

JASO	M315, Class 1A	DTFR	13C150
AISIN-WARNER	JWS 3309	DTFR	13C170
AISIN-WARNER	JWS 3314	DTFR	13C180
AISIN-WARNER	JWS 3317	DTFR	38B100
ALFA ROMEO	HP20	FIAT	9.55550-AV1
ALLISON	C4	FIAT	9.55550-AV4
ALLISON	TES 295	FORD	MERCON
ALLISON	TES 389	FORD	MERCON V
BMW	81 22 9 400 275	FORD	WSS-M2C195-A
BMW	81 22 9 401 220	FORD	WSS-M2C919-E
BMW	83 22 0 024 359	FORD	WSS-M2C922-A1
BMW	83 22 0 026 922	GM	DEXRON II
BMW	83 22 0 403 248	GM	DEXRON II-D
BMW	83 22 0 403 249	GM	DEXRON II-E
BMW	83 22 2 344 206	GM	DEXRON III
BMW	83 22 2 355 599	GM	DEXRON III-G
BMW	83 22 9 407 765	GM	DEXRON III-H
BMW	83 22 9 407 807	HONDA	ATF Z-1
BMW	ATF 4	HYUNDAI	ATF RED 1K
BMW	ATF 6	HYUNDAI	SP-II
BMW	ETL 7045E	HYUNDAI	SP-III
BMW	ETL 8072B	ISUZU	PSF
BMW	LA 2634	JAGUAR	ATF 3403 M115
BMW	LT 71141	JAGUAR	JLM 20238
CHRYSLER	AS68RC ATF	JAGUAR	JLM 20292 (LA 3403-M115)
CHRYSLER	ATF +3 AND +4	JAGUAR	JLM 21044
CHRYSLER	MS 9602	KIA	SP-II
DTFR	13C100	KIA	SP-III
DTFR	13C110	LAND ROVER	LR002748
DTFR	13C120	LAND ROVER	N402
DTFR	13C140	MAZDA	ATF F-1

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



MAZDA	ATF M-V (Type M5)	NISSAN	MATIC-K
MB	236.1	NISSAN	MATIC-W
MB	236.10	PORSCHE	000.043.204.63
MB	236.11	PORSCHE	000.043.205.09
MB	236.12	PORSCHE	999.917.547.00(A2)
MB	236.14	PORSCHE	LA 3403-M115
MB	236.2	PSA	P/N Z 000169756
MB	236.3	RENAULT	MATIC-D2
MB	236.5	TOYOTA	TYPE T
MB	236.6	TOYOTA	TYPE T-III
MB	236.7	TOYOTA	TYPE T-IV
MB	236.8	VOLVO Constr. Equip. (VCE)	1273,41
MB	236.9	VOLVO	1161540
MB	236.91	VW	G 052 025
MINIBUS	4030401	VW	G 052 055
MITSUBISHI	ATF J2	VW	G 052 162
MITSUBISHI	Diaqueen ATF-PA	VW	G 052 533
MITSUBISHI	SFU	VW	G 052 990
MITSUBISHI	V5AWF	VW	G 055 025
MOPAR	ATF +3	VW	G US 000 162
MOPAR	ATF +4	ZF	TE-ML 11A
NISSAN	D3m	ZF	TE-ML 11B
NISSAN	MATIC-D	ZF	TE-ML 14A
NISSAN	MATIC-J		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	36.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	6.84
Viscosity index	ASTM D2270		150
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	218
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

