

WOLF ECOTECH MULTI VEHICLE ATF FE

11/11/2025
3014

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions with a high viscosity index, excellent oxidation stability, excellent friction and anti-wear properties providing excellent fuel economy and meeting the requirements of most American, Japanese and European manufacturers.

APPLICATIONS

Its versatile nature guarantees it can be used in the latest generations of automatic transmissions and torque converters for most passenger cars, off-road vehicles and SUVs.

FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: significantly extended transmission life
Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

AISIN-WARNER	AW-1	HONDA	DPSF2
AISIN-WARNER	AW-2	HONDA	DW-1
AISIN-WARNER	JWS 3324	HYUNDAI	NWS-9638 T5
ALLISON	C4	HYUNDAI	SPH-IV
BMW	000 043 306 24	HYUNDAI	SP-IV
BMW	83 22 0 397 114	ISUZU	WSI
BMW	83 22 2 305 397	JAGUAR	02JDE26444
BMW	83 22 9 407 858	LAND ROVER	LR023288
BMW	83222152426	MAZDA	FZ
BMW	83222167718	MB	236.12
BMW	83222413477	MB	236.14
BMW	958 300 540 00	MB	236.41
BMW	ATF 3	MINIBUS	ATF J3
BMW	ATF 6	MITSUBISHI	Diaqueen ATF-PA
BMW	ATF 7	NISSAN	MATIC-S
BMW	L 12108	PSA	1635056080
BMW	M-1375.4	TESLA	ATF9/EDF2
CHRYSLER	68157995AA	TOYOTA	AUTO FLUID WS
FIAT	9.55550-AV2	VOLVO	31256774
FIAT	9.55550-AV5	VOLVO	31256775
FORD	MERCON LV	VOLVO	31256776
FORD	MERCON SP	VOLVO	31492172
FORD	WSS-M2C195-A	VOLVO	31492173
FORD	WSS-M2C924-A	VW	G 053 001
FORD	WSS-M2C938-A	VW	G 055 005
GM	DEXRON HP	VW	G 055 162
GM	DEXRON VI	VW	G 055 540
HONDA	DPSF	VW	G 060 162

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	32.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	6.45
Viscosity index	ASTM D2270		156
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	210
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

