31/07/2024 3016

WOLF OFFICIALTECH ATF LIFE PROTECT 8

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6, 8 and 9-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

APPLICATIONS

Exclusively intended for the ZF 6,8 and 9 speed automatic transmissions, as fitted in VW, BMW, Jaguar, Land Rover, Jeep, Chrysler and FIAT group.

FEATURES

Anti-wear protection: significantly extended transmission life Frictional properties: very smooth gear shifting, no vibration Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

08200-9016A	HONDA	ATF TYPE 3.1
ATF TYPE 3.0	JAGUAR	02JDE26444
L 12108	LAND ROVER	LR023288
83 22 2 289 720	LAND ROVER	LR023289
83 22 2 305 397	MB	236.82
83222152426	MOPAR	68157995AB
83225A12A00	MOPAR	68218925AA
ATF3+	VW	G 055 162
68157995AA	VW	G 060 162
9.55550-AV5	ZF	S671 090 312
08200-9017	ZF	TE-ML 11
	ATF TYPE 3.0 L 12108 83 22 2 289 720 83 22 2 305 397 83222152426 83225A12A00 ATF3+ 68157995AA 9.55550-AV5	ATF TYPE 3.0JAGUARL 12108LAND ROVER83 22 2 289 720LAND ROVER83 22 2 305 397MB83222152426MOPAR83225A12A00MOPARATF3+VW68157995AAVW9.55550-AV5ZF

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm²/s	31.9
Kinematic viscosity at 100°C	ASTM D445	mm²/s	6.32
Viscosity index	ASTM D2270		153
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	210
Colour	VISUAL		GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV G. Gilliotstraat 52 – 2620 Hemiksem – Belgium Tel. +32 (0)3 870 00 00 www.wolflubes.com

