

# WOLF OFFICIALTECH ATF LIFE PROTECT 8

11/11/2025  
3016

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6, 8 and 9-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

## APPLICATIONS

Exclusively intended for the ZF 6,8 and 9 speed automatic transmissions, as fitted in VW, BMW, Jaguar, Land Rover, Jeep, Chrysler and FIAT group.

## FEATURES

Anti-wear protection: significantly extended transmission life

Frictional properties: very smooth gear shifting, no vibration

Extended oil life: excellent thermal and oxidation stability

## SPECIFICATIONS

ACURA	08200-9016A	JAGUAR	02JDE26444
ACURA	ATF TYPE 3.0	LAND ROVER	LR023288
ATF	L 12108	LAND ROVER	LR023289
BMW	83 22 2 289 720	MB	236.82
BMW	83 22 2 305 397	MOPAR	68157995AB
BMW	83222152426	MOPAR	68218925AA
BMW	83225A12A00	NISSAN	MATIC-R
BMW	ATF3+	VW	G 055 162
CHRYSLER	68157995AA	VW	G 060 162
FIAT	9.55550-AV5	ZF	S671 090 312
HONDA	08200-9017	ZF	TE-ML 11
HONDA	ATF TYPE 3.1		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	31.9
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	6.32
Viscosity index	ASTM D2270		153
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	210
Colour	VISUAL		GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

