

# WOLF OFFICIALTECH MULTI VEHICLE ATF HD-ND

27/06/2025  
3018

This automatic transmission fluid is a high performance heavy duty synthetic transmission fluid. It is designed to deliver normal drain capabilities up to 60 000 km. It contains high quality synthetic base oils and an advanced additive technology. It is suitable for use in automatic transmission systems in both heavy duty trucks and buses.

## APPLICATIONS

This automatic transmission fluid is designed for extended drain intervals for heavy duty trucks and buses as well as off-road equipment.

## FEATURES

Frictional properties: smooth shift performance.  
Extended oil life: excellent thermal and oxidation stability.  
Anti-wear protection: extended transmission life.

## SPECIFICATIONS

ALLISON	C4	VOITH	H55.6335xx
ALLISON	TES 295	VOLVO	STD 1273,40 (97340)
DTRF	13C170	VOLVO	STD 1273,41 (97341)
FORD	MERCON	ZF	TE-ML 03D
GM	DEXRON III-H	ZF	TE-ML 04D
MAN	339 L1	ZF	TE-ML 14A
MAN	339 V1/Z1	ZF	TE-ML 14B
MAN	339 V2/Z2	ZF	TE-ML 14C
MAN	339 Z11	ZF	TE-ML 16L
MAN	339 Z3	ZF	TE-ML 17C
MB	236.9	ZF	TE-ML 20B
VOITH	approval H55.6336xx		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	42.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	8.4
Viscosity index	ASTM D2270		181
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	18000
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

