

WOLF ECOTECH CVT FLUID

28/05/2024
3020

This is a full synthetic lubricant based on carefully selected very high quality base oils, that has been designed to be used in most CVT gearboxes. It is suitable for continuously variable transmissions, using steel push-belts or chains. It offers outstanding anti-wear protection and stable friction characteristics.

APPLICATIONS

OEMs usually recommend specific CVT fluids for their transmissions. By carefully balancing base oils and advanced additives, it has become possible to formulate this fluid that meets the requirements of both European and Japanese CVT manufacturers. This product may not be used in some hybrid vehicles, requiring special fluids.

FEATURES

Anti-wear protection: significantly extended transmission life

Frictional properties: very smooth gear shifting, no vibration

Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

AUDI	TL 52180	mitsubishi	CVTF J-4+
BMW	83 22 2 344 207	NISSAN	NS-1/NS-2/NS-3/Matic W
BMW	ATF 5	PUNCH	EZL799/EZL799A
BMW	EZL799/EZL799A	RENAULT	CVT CK/SK/FK
DAIHATSU	AMIX CVTF DFC	RENAULT	ELFMATIC
DAIHATSU	AMIX CVTF DFE	SUBARU	e-CVTF
DAIHATSU	AMIX CVTF DTC	SUBARU	High Torque CVTF
DAIHATSU	AMIX CVTF-DC	SUBARU	i-CVTF
DAIHATSU	FLUID TC	SUBARU	i-CVTF FG
DODGE	NS-2/CVTF+4	SUBARU	Lineartronic CV-30
FORD	CVT23	SUBARU	Lineartronic CVTF II
FORD	CVT30	SUZUKI	CVTF 3320
FORD	MERCON C	SUZUKI	CVTF 4401
FORD	WSS-M2C928-A	SUZUKI	CVTF GREEN 2
FORD	WSS-M2C933-A	SUZUKI	NS-2/SHELL GREEN 1 V
FUJIIYUUKO	i-CVTF FG	TOYOTA	CVT FE
GM	CVTF GREEN 2/SATURN DEX-CVT	TOYOTA	TC
HONDA	HCF-2/HMMF (No Start Clutch)	VOLVO	CVT 4959
HYUNDAI	SP-CVT1	VW	G 052 180
JEEP	NS-2/CVTF+4	VW	G 052 516
KIA	SP-CVT 1		
MAZDA	CVTF 3320		
MB	236.20/CVT28		
MINI	EZL799/EZL799A/CVT V1		
mitsubishi	CVTF ECO J4		
mitsubishi	CVTF J-1		
mitsubishi	CVTF J-4		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.844
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	32.9
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7.1
Viscosity index	ASTM D2270		187
Pour point	ASTM D6892	°C	-54
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	10600
Flash Point COC	ASTM D92	°C	188
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

