

WOLF ECOTECH CVT-ATF FLUID

18/10/2024
3029

This is a multifunctional full synthetic lubricant that has been designed for both CVT and step automatic transmissions. The multi-vehicle suitability of this oil enables optimized supply chain, reduced operational cost and mitigated misapplication risk.

It offers outstanding anti-wear protection and stable friction characteristics.

APPLICATIONS

It is suitable for continuously variable transmissions (using steel push-belts or chains) and for the latest generation of high efficiency step automatic transmissions where the manufacturer recommends the specifications as referred to in the extensive list on this technical data sheet.

FEATURES

Anti-wear protection: significantly extended transmission life.

Extended oil life: excellent thermal and oxidation stability.

Frictional properties: very smooth gear shifting, no vibration.

SPECIFICATIONS

ACURA	ATF-Z1	DAIHATSU	AMIX CVTF-DC
AIISIN-WARNER	AW-1	DAIHATSU	AMMIX ATF D II
AIISIN-WARNER	AW-2	DAIHATSU	AMMIX ATF D III SP
AIISIN-WARNER	JWS 3309(T-IV)	DAIHATSU	FLUID TC
AIISIN-WARNER	JWS 3324(W5)	DODGE	NS-2/CVTF+4
AUDI	TL 52180	FIAT	T-IV type
BMW	83 22 2 344 207	FORD	CVT23
BMW	83 22 9 407 765	FORD	CVT30
BMW	ATF 5	FORD	ESP-M2C166-H
BMW	ATF 6	FORD	FRN 5
BMW	ETL 7045E	FORD	MERCON
BMW	ETL 8072B	FORD	MERCON C
BMW	EZL799/EZL799A	FORD	MERCON SP
BMW	JWS 3309(T-IV)	FORD	WSS-M2C922-A1
BMW	LA 2634	FORD	WSS-M2C924-A
BMW	LT 71141	FORD	WSS-M2C928-A
BMW	ZF 5HP18FL,5HP24,5HP30	FORD	WSS-M2C933-A
BOSCH REXROTH	TE-ML 09	FORD	XT-2 QSM (Syn)
CATERPILLAR	TO-2	FORD	XT-2QDX (M)
CHRYSLER	ATF +, +2, +3	FORD	XT-6-QSP
CHRYSLER	Dodge MOPAR AS 68 RC (T-IV) , JWS 3309	FUJIIYUUKO	i-CVTF FG
CHRYSLER	Dodge/Jeep/ 68043742AA	FUSO	ATF -SP III
DAEWOO	LT 71141	FUSO	ATF-A4
DAIHATSU	AMIX CVTF DFC	FUSO	ATF-II
DAIHATSU	AMIX CVTF DFE	GEELY	CVTF-EX1
DAIHATSU	AMIX CVTF DTC	GM	1940700
		GM	1940767

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



GM	21005966	MAZDA	CVTF 3320
GM	22717466	MB	236.20/CVT28
GM	88863400	MINI	EZL799/EZL799A/CVT V1
GM	88863401	MINI	T-IV
GM	88900925	MITSUBISHI	CVTF ECO J4
GM	93160393	MITSUBISHI	CVTF J-1
GM	9985010	MITSUBISHI	CVTF J-4
GM	9985835	MITSUBISHI	CVTF J-4+
GM	9986195	MITSUBISHI	Diaqueen ATF PA
GM	AW-1	MITSUBISHI	Diaqueen AW
GM	CVTF GREEN 2/SATURN DEX-CVT	MITSUBISHI	Diaqueen J2
GM	DEXRON II	MITSUBISHI	Diaqueen J3
GM	DEXRON II-D	MITSUBISHI	Diaqueen SK
GM	DEXRON II-E	MITSUBISHI	Diaqueen SP
GM	DEXRON III-G	MITSUBISHI	Diaqueen SP-II
GM	DEXRON III-H	MITSUBISHI	Diaqueen SP-III
GM	DEXRON TYPE A, SUFFIX A	MITSUBISHI	Diaqueen SP-IV
HINO	Blue Ribon ATF	NISSAN	MATIC-C
HONDA	ATF Z-1	NISSAN	MATIC-D
HONDA	DW-1	NISSAN	MATIC-J
HONDA	HCF-2/HMMF (No Start Clutch)	NISSAN	MATIC-K
HONDA	Type 3.0 and 3.1	NISSAN	MATIC-S
HONDA	Ultra HEVF-Type 1	NISSAN	NS-1/NS-2/NS-3/Matic W
HYUNDAI	040000C905G	PORSCHE	000.043.205.09
HYUNDAI	Dex-II/SP-II	PORSCHE	000.043.205.28
HYUNDAI	SP-CVT1	PORSCHE	999.917.547.00(A2)
HYUNDAI	SP-II M	PORSCHE	LA 3403-M115
HYUNDAI	SP-III	PORSCHE	T-IV (JWS 3309)
HYUNDAI	SP-IV M	PORSCHE	Z 000169756
HYUNDAI	SP-IV M1	PSA	1635056080
ISUZU	08200-9001	PSA	B71 2340
ISUZU	BESCO ATF-II	PSA	P/N Z 000169756
ISUZU	BESCO ATF-III	PSA	ZF 4HP20
ISUZU	BESCO ATF-SP	PUNCH	EZL799/EZL799A
ISUZU	SCS Fluid	RENAULT	CVT CK/SK/FK
JAGUAR	ATF 3403 JLM 20238	RENAULT	DPO/AL4
JAGUAR	ATF 3403 M115	RENAULT	ELFMATIC
JAGUAR	JLM 20292	RENAULT	MATIC-D2
JAGUAR	LT71141 ZF 5HP24	RENAULT	Samsung SATF-D
JASO	M315-2013 1A	SAAB	93 160 393
JASO	M315-2013 1A-LV	SAAB	93 165 147
JASO	M315-2013 2A	SAAB	T-IV (JWS 3309)
JEEP	ATF +3	SCION	(all Vehicles)
JEEP	NS-2/CVTF+4	SSANG YONG	DSIH 5M-66
KIA	SP-CVT 1	SUBARU	ATF
LEXUS	JWS 3309	SUBARU	ATF 5AT
MAZDA	ATF 3317	SUBARU	ATF, ATF HP
MAZDA	ATF A7	SUBARU	DEXRON-II
MAZDA	ATF D-II	SUBARU	e-CVTF
MAZDA	ATF F-1	SUBARU	High Torque CVTF
MAZDA	ATF FZ	SUBARU	i-CVTF
MAZDA	ATF M-III	SUBARU	i-CVTF FG
MAZDA	ATF M-V (Type M5)	SUBARU	K0140Y0700
MAZDA	ATF N-1	SUBARU	Lineartronic CV-30
MAZDA	ATF S-1	SUBARU	Lineartronic CVTF II

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



SUZUKI	AT OIL 5D06	VOLVO	97335
SUZUKI	ATF 2326	VOLVO	CE 97340
SUZUKI	ATF 2384K	VOLVO	CE 97341
SUZUKI	ATF 3314	VOLVO	CVT 4959
SUZUKI	ATF 3317	VW	5HP (18FL, 30)
SUZUKI	ATF AW-1	VW	5HP (19FL, 24A)
SUZUKI	ATF JWS 3309	VW	5HP (ZF 5 HP 30)
SUZUKI	CVTF 3320	VW	G 052 025
SUZUKI	CVTF 4401	VW	G 052 055
SUZUKI	CVTF GREEN 2	VW	G 052 162
SUZUKI	NS-2/SHELL GREEN 1 V	VW	G 052 180
TOYOTA	ATF D-II	VW	G 052 516
TOYOTA	ATF D-III	VW	G 052 990
TOYOTA	ATF WS	VW	G 053 001
TOYOTA	CVT FE	VW	G 053 025
TOYOTA	TC	VW	G 053 162 A1
TOYOTA	TYPE T	VW	G 055 025
TOYOTA	TYPE T-III	VW	G 055 540
TOYOTA	TYPE T-IV	VW	TL 52540-A
VOLVO	1161521	ZF	TE-ML 05L
VOLVO	1161540/1161640	ZF	TE-ML 09X
VOLVO	97325	ZF	TE-ML 21L

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm²/s	36.5
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.5
Viscosity index	ASTM D2270		179
Pour point	ASTM D6892	°C	-51
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	15000
Flash Point COC	ASTM D92	°C	190
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

