

# WOLF RACING TRANS/AXLE 75W-90 ESTER

06/09/2024  
65525

This advanced sustainable RRBO transmission oil, fortified with ester and PAO, is especially developed for racing vehicles.

The oil's excellent viscosity at low temperatures guarantees quick protection of all gears.

## APPLICATIONS

This is a special sustainable RRBO transmission oil with extreme pressure properties, specifically composed for use in extreme racing circumstances.

## FEATURES

Frictional properties: very smooth gear shifting, no vibration.

Anti-wear protection: extended transmission life.

Extended oil life: superior thermal and oxidation stability.

## SPECIFICATIONS

API	GL-5	SCHMIDT	SFU
API	MT-1	ANTRIEBSTECHNIK	
ARVIN MERITOR	0-76-E	X-TRAC	SFU
BMW	OSP	ZF	TE-ML 05A
CHRYSLER	MS 9763	ZF	TE-ML 05B
DANA	SFU	ZF	TE-ML 07A
FIAT	9.55550-DA3	ZF	TE-ML 12N
FIAT	9.55550-DA4	ZF	TE-ML 16F
FIAT	9.55550-DA6	ZF	TE-ML 17B
FIAT	9.55550-DA7	ZF	TE-ML 19C
FIAT	9.55550-MX4	ZF	TE-ML 21A
HEWLAND	SFU		
HOLLINGER	SFU		
MACK	GO-J		
MCLAREN	MOB PTX		
PORSCHE	000.043.204.19		
PORSCHE	000.043.204.20		
PORSCHE	000.043.204.71		
PORSCHE	000.043.207.76		
PORSCHE	000.043.210.12		
PORSCHE	000.043.304.71		
PORSCHE	000.043.305.55		
PORSCHE	999.917.062.00		
PORSCHE	999.917.067.00		
PORSCHE	999.917.090.00		
PORSCHE	999.917.545.00		
PORSCHE	999.917.546.00		
RICARDO	SFU		
SADEV	SFU		
SCANIA	STO 2:0A FS		

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)



## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.881
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	104
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	15.4
Viscosity index	ASTM D2270		156
Pour point	ASTM D6892	°C	-51
Colour	VISUAL		LIGHT BROWN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

