

WOLF OFFICIALTECH 10W40 UHPD EXTRA

12/12/2023
65636

The state of the art wear-reducing additives contained within this synthetic engine oil are engineered to combine stable oil performance with excellent engine protection, resulting in extended drain intervals. The protective oil film retains its excellent properties over a wide range of temperatures. Furthermore, the engine oil has high shear resistance, cutting down on maintenance costs by further extending drain intervals.

APPLICATIONS

Both off- and on-road heavy-duty applications with or without turbochargers, superchargers or after-treatment systems can be serviced with this engine oil. It meets the specifications of a wide range of high-demanding specifications including the Volvo VDS-4.5. Thanks to its backward compatibility, this versatile engine oil can be used in both modern and older engines. It is compatible with emission control technology EURO IV, V and VI.

FEATURES

Aftertreatment protection: full aftertreatment system protection.
Total engine protection: outstanding engine cleanliness and durability.
Fuel economy: lower fuel consumption and CO2 emissions.

SPECIFICATIONS

ACEA	E11	DAIMLER TRUCK	approval DTFR 15C110
ACEA	E4	DAIMLER TRUCK	approval DTFR 15C120
ACEA	E6-16	DAIMLER TRUCK	DTFR 13D110
ACEA	E7	DAIMLER TRUCK	DTFR 15C100
ACEA	E8	DETROIT DIESEL	DFS 93K215
ACEA	E9-16	DETROIT DIESEL	DFS 93K218
API	CI-4	DETROIT DIESEL	DFS 93K222
API	CI-4 Plus	DEUTZ	approval DQC-IV-18 LA
API	CJ-4	DEUTZ	DQC IV-10 LA
API	CK-4	DEUTZ	TTCD
JASO	DH-1	FORD	WSS-M2C171-F1
JASO	DH-2-17	IVECO	18-1804 Classe T2 E7
ALLISON	C4	IVECO	18-1804 Classe TLS E6
CASE	MAT 3571	IVECO	18-1804 Classe TLS E9
CASE	MAT 3572	JD	JDQ-78X
CATERPILLAR	ECF-1a	LIEBHERR	LH-00-ENG5C LA
CATERPILLAR	ECF-2	MACK	approval EO-S 4.5
CATERPILLAR	ECF-3	MACK	EO-M PLUS
CATERPILLAR	TO-2	MACK	EO-N
CUMMINS	CES 20076	MACK	EO-N Premium Plus
CUMMINS	CES 20077	MACK	EO-O Premium Plus
CUMMINS	CES 20078	MAN	M3271-1
CUMMINS	CES 20081	MAN	M3477
CUMMINS	CES 20086	MAN	M3575
DAF	EXTENDED DRAIN	MAN	M3775

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



MB	228.31	RENAULT	RLD-2
MB	235.28	RENAULT	RLD-4
MB	approval 228.51	RENAULT	RXD
MB	approval 228.52	SCANIA	LA
MTU	approval Oil Category 3.1	VOITH	Retarder Oil Class B
MTU	Oil Category 2.1	VOLVO	approval VDS-4.5
RENAULT	approval RLD-3	VOLVO	VDS-3
RENAULT	RGD	VOLVO	VDS-4
RENAULT	RLD		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.859
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	86.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.3
Viscosity index	ASTM D2270		156
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	13.4
Pour point	ASTM D6892	°C	-36
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

