

# WOLF OFFICIALTECH 5W30 UHPD FE+

13/11/2024  
65649

This full synthetic engine oil is your number one choice to service the most fuel-efficient engines by providing up to 2.2 % increase in fuel economy versus a 15W40 lubricant. It offers complete engine protection thanks to its wear reducing additives, enabling a unique balance between protection and fuel economy. Furthermore, its improved oxidation control and shear stability guarantee maximum fuel economy during the complete oil change interval.

## APPLICATIONS

It offers complete servicing of fuel-efficient HD engines requiring advanced FA-4 engine oils. It specifically meets the requirements of the Mercedes-Benz 228.61 specification.

## FEATURES

Fuel economy: superior fuel economy and CO2 reduction.  
Total engine protection: outstanding engine cleanliness and durability.  
: Aftertreatment protection

## SPECIFICATIONS

ACEA	F01	DETROIT DIESEL	DFS 93K223
API	FA-4	JASO	DH-2F
API	SN	MACK	EOS-5
API	SN Plus	MB	approval 228.61
JASO	DH-2	RENAULT	RLD-5
CUMMINS	CES 20087	VOLVO	VDS-5
DAIMLER TRUCK	approval DTRF 15C130		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	58.5
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.9
Viscosity index	ASTM D2270		156
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	9.8
Pour point	ASTM D6892	°C	-33
Sulfated Ash	ASTM D874	Mass %	0.98
Flash Point COC	ASTM D92	°C	220
Colour	VISUAL		DARK BROWN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

**WOLF OIL CORPORATION NV**  
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00  
[www.wolf lubes.com](http://www.wolf lubes.com)

