

WOLF VITALTECH 10W-50 F-A

14/08/2023
65650

This ester and PAO synthetic based racing oil is fortified with a precisely balanced component-blended additive system delivering high levels of anti-wear and friction reducing characteristics. This advanced protection is engineered to help deliver optimum horsepower.

APPLICATIONS

This advanced ester and PAO synthetic based racing oil is specifically designed to meet the Abarth 0101 specification. This high performance lubricant is designed to offer excellent friction reduction.

FEATURES

Total engine protection: performance in keeping the engine clean.
Driving style: racing.

PERFORMANCE

| | | | |
|------|---------|----------|-------------|
| ACEA | C3 | CHRYSLER | MS 10725 |
| API | SN Plus | CHRYSLER | MS 12633 |
| API | SP | Fiat | ABARTH 0101 |
| API | SP/RC | | |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|---------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.854 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 107 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 17.4 |
| Viscosity index | ASTM D2270 | | 179 |
| B.N. (HClO ₄ method) | ASTM D2896 | mg KOH/g | 9.4 |
| Pour point | ASTM D6892 | °C | -54 |
| Flash Point COC | ASTM D92 | °C | 232 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

