

WOLF OFFICIALTECH OW-20 FXFE

21/03/2025
65662

A low SAPS passenger car engine oil focused on the most Ford engine oil specification WSS-M2C954-A1.

APPLICATIONS

Especially developed for Ford engines where Ford WSS-M2C954-A1 is required.

FEATURES

Aftertreatment protection: full aftertreatment device protection.

Cold start: excellent fluidity at low temperature.

Fuel economy: superior fuel economy and CO2 reduction.

SPECIFICATIONS

FORD WSS-M2C954-A1

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	43
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.5
Viscosity index	ASTM D2270		179
Pour point	ASTM D6892	°C	-36
Sulfated Ash	ASTM D874	Mass %	0.78
Flashpoint PMCC	ASTM D93	°C	202
Density at 15°C	ASTM D4052	g/ml	0.841

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

