

WOLF OFFICIALTECH 5W-30 MS-GD

29/07/2025
65665

This synthetic engine oil guarantees a cleaner and better performing engine without lowering the oil drain interval.

It is based on carefully selected very high quality base oils and formulated using the latest technology for catalyst compatible engine oils.

The broad applicability of this engine oil enables you to offer perfect maintenance to different vehicles of several major brands.

APPLICATIONS

This engine oil can be used in systems with or without exhaust gas aftertreatment where C2 (PSA) or C3 (German OEM's) engine oils are required.

Furthermore, this engine oil has an official GM dexosD approval. DexosD meets or exceeds the performance of dexos2 and is backward compatible.

FEATURES

Aftertreatment protection: full aftertreatment device protection.

Fuel economy: lower fuel consumption and CO2 emissions.

Total engine protection: outstanding engine cleanliness and durability.

SPECIFICATIONS

ACEA	C2
ACEA	C3
API	SN/CF
BMW	LOGLIFE-04
CHRYSLER	MS 11106
FIAT	9.55535-S3
FORD	WSS-M2C917-A
GM	dexos2™
GM	dexos™D
HYUNDAI	SFU
KIA	SFU
MB	226.5
MB	229.31
MB	229.51
MB	229.52
OPEL	GM-LL-A-025
OPEL	GM-LL-B-025
RENAULT	RN 0700
RENAULT	RN 0710
VW	502 00 < 2017
VW	505 00
VW	505 01

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	75.56
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	12.4
Viscosity index	ASTM D2270		163
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	8.0
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

