

WOLF OFFICIALTECH ATF MB FE

19/06/2023
3013

This is a full synthetic lubricant based on carefully selected very high quality base oils, intended for the latest MB 7-speed automatic transmissions from MB (NAG2FE+). It provides excellent frictional durability, superior performance and fuel economy.

APPLICATIONS

This product is recommended for sports vehicles (NAG2FE+) and is not backwards compatible with the previous 5- and 7- speed transmissions , which require MB 236.10, 236.12, 236.14.

FEATURES

Anti-wear protection: significantly extended transmission life

Frictional properties: very smooth gear shifting, no vibration

Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

MB 236.15

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.847
Kinematic viscosity at 40°C	ASTM D445	mm²/s	20.9
Kinematic viscosity at 100°C	ASTM D445	mm²/s	4.79
Viscosity index	ASTM D2270		158
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	3500
Flash Point COC	ASTM D92	°C	178
Colour	VISUAL		DARK BLUE

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

