

WOLF OFFICIALTECH OW-16 RXFE

14/04/2025
65661

This full synthetic engine oil is especially developed for Renault gasoline engines where Renault AN2022 is required.

Thanks to its low viscosity and outstanding fluidity this oil significantly reduces wear and ensures fuel savings and lower CO2 emissions. Optimized additive package reduces soot and deposits and keeps the engine clean.

APPLICATIONS

Especially developed for Renault gasoline engines where Renault AN2022 is required.

FEATURES

Cold start: excellent fluidity at low temperature.

Fuel economy: superior fuel economy and CO2 reduction.

Total engine protection: performance in keeping the engine clean.

SPECIFICATIONS

API	SP	RENAULT	AN2022
ILSAC	GF-6 B		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.841
Kinematic viscosity at 40°C	ASTM D445	mm²/s	26.95
Kinematic viscosity at 100°C	ASTM D445	mm²/s	6.4
Viscosity index	ASTM D2270		206
Flash Point COC	ASTM D92	°C	243
Pour point	ASTM D6892	°C	-45
Sulfated Ash	ASTM D874	Mass %	0.8

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

