

CHAMPION OEM SPECIFIC

80W-90 LS GL 5 ZF-N

This high performance ZF 05N/21N gear oil is an advanced all-round lubricant, which is balanced to lubricate a wide range of axles including the ones equipped with limited slip (LS) and hypoid gears. Its formula offers outstanding extreme-pressure resistance, which is proven by its typical phosphorus content of 2000 ppm.

APPLICATIONS

This officially approved ZF 05N/21N formula can be used to service axles with or without limited slip differential or multi-disc differential. Furthermore, it suits the needs of different axles and differentials with or without hypoid drive. This multi-use gear oil can be used within dumpers, wheel loaders, mobile excavators, tractor axles, planetary final drives and even in certain rail vehicles & bus transmission systems with multi-disc self-locking differentials. This innovative lubricant allows you to make fleet maintenance more efficient by reducing the amount of different fluids you need.

FEATURES

Phosphorus content of 2000 ppm: advanced extreme-pressure resistance

Broad applicability: easier fleet maintenance with this all-round product

Improved component cleanliness: prevent slip disks and gears from experiencing additional wear

SPECIFICATIONS

API	GL-5	ZF	approval TE-ML 05N
API	MT-1	ZF	approval TE-ML 21N
ARVIN MERITOR	AXLES	ZF	TE-ML 05C
FORD	WSS-M2C197-A+M2C118-A	ZF	TE-ML 07A
GM	1942382	ZF	TE-ML 08
GM	1942387	ZF	TE-ML 12C
GM	9121965	ZF	TE-ML 16E
JD	JDM J11F	ZF	TE-ML 21C
MACK	GO-J		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.880
Kinematic viscosity at 40°C	ASTM D445	mm²/s	131
Kinematic viscosity at 100°C	ASTM D445	mm²/s	14.2
Viscosity index	ASTM D2270		115
A.N. [Colorimetric]	ASTM D974	mg KOH/g	1.20
Pour point	ASTM D6892	°C	-36
Phosphorus	ASTM D5185	mg/kg	2000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

