CHAMPION ACTIVE DEFENCE 15W40 SN/CF

This is a very high-quality mineral oil with proven performance. It has been upgraded to meet and exceed ACEA A3/B4. It is suitable for most 4-stroke gasoline and diesel cars as well as light trucks.

APPLICATIONS

4-stroke gasoline passenger cars engines (multi-valve, turbo, etc.); 4-stroke diesel engines, with or without turbo. High compatibility with biodiesel, based on extensive field trials.

FEATURES

Total engine protection: engine protection and cleanliness.

PERFORMANCE

| ACEA | A3/B4 | PSA | B71 2295 |
|------|------------|---------|----------|
| API | SN/CF | RENAULT | RN 0700 |
| FIAT | 9.55535-D2 | RENAULT | RN 0710 |
| FIAT | 9.55535-G2 | VW | 50101 |
| МВ | 229.1 | vw | 505 00 |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|----------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.877 |
| Kinematic viscosity at 40°C | ASTM D445 | mm²/s | 99.4 |
| Kinematic viscosity at 100°C | ASTM D445 | mm²/s | 13.8 |
| Viscosity index | ASTM D2270 | | 140 |
| B.N. (HCLO4 method) | ASTM D2896 | mg KOH/g | 10.1 |
| Pour point | ASTM D6892 | °C | -33 |
| Flash Point COC | ASTM D92 | °C | 218 |
| | | | |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

