

# CHAMPION OEM SPECIFIC 10W-30 IL

Thanks to the low viscosity and excellent fluidity, this oil offers low wear, low emissions, and a strong fuel economy. Its carefully synthesized additive package targets soot and deposits to keep the engine clean.

## APPLICATIONS

This engine oil has been specifically developed to meet the challenging requirements of the latest ILSAC GF-7 A standard where fuel economy and CO<sub>2</sub> reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

## FEATURES

*Cold start: excellent fluidity at low temperature*

*Fuel economy: excellent fuel economy and low exhaust emissions*

*Total engine protection: performance in keeping the engine clean*

## SPECIFICATIONS

API	SN Plus	ILSAC	GF-5
API	SN/RC	ILSAC	GF-6 A
API	SP	ILSAC	GF-7 A
API	SP/RC	CHRYSLER	MS 6395
API	SQ	GM	6094M
API	SQ/RC		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	64.2
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	10.6
Viscosity index	ASTM D2270		155
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	7.4
Pour point	ASTM D6892	°C	-42
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

