

CHAMPION OEM SPECIFIC 10W-30 IL HC

This semi-synthetic oil offers low wear, low emissions, and a strong fuel economy. Its carefully synthesized additive package targets soot and deposits to keep the engine clean.

APPLICATIONS

This engine oil has been specifically developed to meet the challenging requirements of the latest ILSAC GF-7 A standard where fuel economy and CO₂ reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

FEATURES

Cold start: excellent fluidity at low temperature

Fuel economy: excellent fuel economy and low exhaust emissions

Total engine protection: performance in keeping the engine clean

SPECIFICATIONS

API	SN Plus	ILSAC	GF-5
API	SN/RC	ILSAC	GF-6 A
API	SP	ILSAC	GF-7 A
API	SP/RC	CHRYSLER	MS 6395
API	SQ	GM	6094M
API	SQ/RC		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.849
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	64.2
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	10.6
Viscosity index	ASTM D2270		155
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	7.4
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

