

# CHAMPION LIFE EXTENSION

## 85W140 GL 5

This is an extreme-pressure lubricant for gear boxes, specifically formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.

### APPLICATIONS

Recommended for all hypoid transmissions and also suitable for spiral bevel gears, worm wheels and most transaxles.

### FEATURES

Frictional properties: easy gear shifting

Anti-wear protection: long transmission life

### PERFORMANCE

<b>API</b>	GL-5	<b>ZF</b>	TE-ML 16B
<b>MIL</b>	L-2105 C	<b>ZF</b>	TE-ML 16C
<b>MIL</b>	L-2105 D	<b>ZF</b>	TE-ML 16D
<b>ZF</b>	TE-ML 05A	<b>ZF</b>	TE-ML 17B
<b>ZF</b>	TE-ML 07A	<b>ZF</b>	TE-ML 19B
<b>ZF</b>	TE-ML 12E		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.908
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	367
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	26.1
Viscosity index	ASTM D2270		95
Pour point	ASTM D6892	°C	-15
Copper corrosion [150°C, 3h]	ASTM D130		1B
Flash Point COC	ASTM D92	°C	215

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

