

# CHAMPION OEM SPECIFIC GL-4 75W-90 V

This is a full synthetic high-performance long drain, severe service manual transmission fluid capable of extending oil drain intervals to 800.000 kilometers.

## APPLICATIONS

This severe service manual transmission fluid can be used in all overdrive Volvo I-shift transmissions and other heavy duty automated manual transmissions.  
Also suitable for Mack mDrive transmissions.

## FEATURES

Anti-wear protection: significantly extended transmission life.  
Extended oil life: excellent thermal and oxidation stability.

Frictional properties: very smooth shift performance.

## SPECIFICATIONS

<b>API</b>	GL-4	<b>MACK</b>	T0-A PLUS
<b>API</b>	MT-1	<b>NAVISTAR</b>	MPAPS B-6816 TYPE 2
<b>ALLISON</b>	TES 439	<b>VOLVO</b>	97315
<b>ARVIN MERITOR</b>	O-81	<b>VOLVO</b>	97318
<b>EATON</b>	PS-386	<b>VOLVO</b>	97319

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.857
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	103
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	15.7
Viscosity index	ASTM D2270		162
Pour point	ASTM D6892	°C	-45
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium  
Tel. +32 3 870 00 00  
[www.championlubes.com](http://www.championlubes.com)

