CHAMPION NEW ENERGY ATF DIII

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This is an oil with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

APPLICATIONS

This oil is used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements.

FEATURES

Frictional properties: smooth shift performance Anti-wear protection: extended transmission life

Extended oil life: excellent thermal and oxidation stability

PERFORMANCE

ALLISON	C4	VOLVO	STD 1273,35 (97335)
FORD	MERCON	VOLVO	STD 1273,37 (97337)
GM	6417-M DEXRON III-G	VOLVO	STD 1273,40 (97340)
GM	DEXRON II-D	VOLVO	STD 1273,41 (97341)
GM	DEXRON III-H	ZF	TE-ML 03D
MAN	339 V1/Z1	ZF	TE-ML 04D
МВ	236.5	ZF	TE-ML 05L
МВ	236.6	ZF	TE-ML 09
МВ	236.7	ZF	TE-ML 11B
МВ	236.8	ZF	TE-ML 14A
МВ	236.9	ZF	TE-ML 17C
VOITH	H55.6335xx	ZF	TE-ML 21L
VOLVO	STD 1273.25 (97325)		



TYPICAL CHARACTERISTICS

Method	Unit	Average results
ASTM D4052	g/ml	0.847
ASTM D445	mm²/s	33.9
ASTM D445	mm²/s	7.1
ASTM D2270		179
ASTM D6892	°C	-45
ASTM D2983	mPa.s	17500
ASTM D92	°C	196
VISUAL		RED
	ASTM D4052 ASTM D445 ASTM D445 ASTM D2270 ASTM D6892 ASTM D2983 ASTM D92	ASTM D4052 g/ml ASTM D445 mm²/s ASTM D445 mm²/s ASTM D2270 ASTM D6892 °C ASTM D2983 mPa.s ASTM D92 °C

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.



G. Gilliotstraat 52 - 2620 Hemiksem - Belgium Tel. +32 3 870 00 00 www.championlubes.com

