

CHAMPION **ECO FLOW** MULTI VEHICLE ATF FE

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions with a high viscosity index, excellent oxidation stability, excellent friction and anti-wear properties providing excellent fuel economy and meeting the requirements of most American, Japanese and European manufacturers.

APPLICATIONS

Its versatile nature guarantees it can be used in the latest generations of automatic transmissions and torque converters for most passenger cars, off-road vehicles and SUVs.

FEATURES

Frictional properties: very smooth gear shifting, no vibration

Anti-wear protection: significantly extended transmission life

Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

 AISIN-WARNER	AW-1	 HYUNDAI	SPH-IV
 AISIN-WARNER	AW-2	 HYUNDAI	SP-IV
 AISIN-WARNER	JWS 3324	 ISUZU	WSI
 BMW	000 043 306 24	 JAGUAR	02JDE26444
 BMW	83 22 0 397 114	 LAND ROVER	LR023288
 BMW	83 22 2 305 397	 MAZDA	FZ
 BMW	83 22 9 407 858	 MB	236.12
 BMW	83222152426	 MB	236.14
 BMW	83222167718	 MB	236.41
 BMW	83222413477	 MITSUBISHI	ATF J3
 BMW	958 300 540 00	 MITSUBISHI	Diaqueen ATF PA
 BMW	ATF 3	 NISSAN	MATIC-S
 BMW	ATF 6	 PSA	1635056080
 BMW	ATF 7	 TESLA	ATF9/EDF2
 BMW	L 12108	 TOYOTA	AUTO FLUID WS
 BMW	M-1375.4	 VOLVO	31492172
 CHRYSLER	68157995AA	 VOLVO	31492173
 FIAT	9.55550-AV2	 VW	G 053 001
 FIAT	9.55550-AV5	 VW	G 055 005
 FORD	MERCON LV	 VW	G 055 162
 FORD	MERCON SP	 VW	G 055 540
 FORD	WSS-M2C195-A	 VW	G 060 162
 FORD	WSS-M2C924-A		
 FORD	WSS-M2C938-A		
 GM	DEXRON HP		
 GM	DEXRON VI		
 HONDA	DPSF		
 HONDA	DPSF2		
 HONDA	DW-1		
 HYUNDAI	NWS-9638 T5		

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION
LUBRICANTS



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	32.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	6.45
Viscosity index	ASTM D2270		156
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	210
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

