

# CHAMPION **ECO FLOW** MULTI VEHICLE ATF FE

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions with a high viscosity index, excellent oxidation stability, excellent friction and anti-wear properties providing excellent fuel economy and meeting the requirements of most American, Japanese and European manufacturers.

## APPLICATIONS

Its versatile nature guarantees it can be used in the latest generations of automatic transmissions and torque converters for most passenger cars, off-road vehicles and SUVs.

## FEATURES

Frictional properties: very smooth gear shifting, no vibration

Anti-wear protection: significantly extended transmission life

Extended oil life: excellent thermal and oxidation stability

## SPECIFICATIONS

<b>AISIN-WARNER</b>	AW-1	<b>HYUNDAI</b>	NWS-9638 T5
<b>AISIN-WARNER</b>	AW-2	<b>HYUNDAI</b>	SPH-IV
<b>AISIN-WARNER</b>	JWS 3324	<b>HYUNDAI</b>	SP-IV
<b>ALLISON</b>	C4	<b>ISUZU</b>	WSI
<b>BMW</b>	000 043 306 24	<b>JAGUAR</b>	02JDE26444
<b>BMW</b>	83 22 0 397 114	<b>LAND ROVER</b>	LR023288
<b>BMW</b>	83 22 2 305 397	<b>MAZDA</b>	FZ
<b>BMW</b>	83 22 9 407 858	<b>MB</b>	236.12
<b>BMW</b>	83222152426	<b>MB</b>	236.14
<b>BMW</b>	83222167718	<b>MB</b>	236.41
<b>BMW</b>	83222413477	<b>MITSUBISHI</b>	ATF J3
<b>BMW</b>	958 300 540 00	<b>MITSUBISHI</b>	Diaqueen ATF-PA
<b>BMW</b>	ATF 3	<b>NISSAN</b>	MATIC-S
<b>BMW</b>	ATF 6	<b>PSA</b>	1635056080
<b>BMW</b>	ATF 7	<b>TESLA</b>	ATF9/EDF2
<b>BMW</b>	L 12108	<b>TOYOTA</b>	AUTO FLUID WS
<b>BMW</b>	M-1375.4	<b>VOLVO</b>	31256774
<b>CHRYSLER</b>	68157995AA	<b>VOLVO</b>	31256775
<b>FIAT</b>	9.55550-AV2	<b>VOLVO</b>	31256776
<b>FIAT</b>	9.55550-AV5	<b>VOLVO</b>	31492172
<b>FORD</b>	MERCON LV	<b>VOLVO</b>	31492173
<b>FORD</b>	MERCON SP	<b>VW</b>	G 053 001
<b>FORD</b>	WSS-M2C195-A	<b>VW</b>	G 055 005
<b>FORD</b>	WSS-M2C924-A	<b>VW</b>	G 055 162
<b>FORD</b>	WSS-M2C938-A	<b>VW</b>	G 055 540
<b>GM</b>	DEXRON HP	<b>VW</b>	G 060 162
<b>GM</b>	DEXRON VI		
<b>HONDA</b>	DPSF		
<b>HONDA</b>	DPSF2		
<b>HONDA</b>	DW-1		

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)





## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	32.5
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	6.45
Viscosity index	ASTM D2270		156
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	210
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

