

# CHAMPION OEM SPECIFIC ATF LIFE PROTECT 8

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6, 8 and 9-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

## APPLICATIONS

Exclusively intended for the ZF 6,8 and 9 speed automatic transmissions, as fitted in VW, BMW, Jaguar, Land Rover, Jeep, Chrysler and FIAT group.

## FEATURES

Anti-wear protection: significantly extended transmission life

Frictional properties: very smooth gear shifting, no vibration

Extended oil life: excellent thermal and oxidation stability

## SPECIFICATIONS

<b>ACURA</b>	08200-9016A	<b>HONDA</b>	ATF TYPE 3.1
<b>ACURA</b>	ATF TYPE 3.0	<b>JAGUAR</b>	02JDE26444
<b>ATF</b>	L 12108	<b>LAND ROVER</b>	LR023288
<b>BMW</b>	83 22 2 289 720	<b>LAND ROVER</b>	LR023289
<b>BMW</b>	83 22 2 305 397	<b>MB</b>	236.82
<b>BMW</b>	83222152426	<b>MOPAR</b>	68157995AB
<b>BMW</b>	83225A12A00	<b>MOPAR</b>	68218925AA
<b>BMW</b>	ATF3+	<b>VW</b>	G 055 162
<b>CHRYSLER</b>	68157995AA	<b>VW</b>	G 060 162
<b>FIAT</b>	9.55550-AV5	<b>ZF</b>	S671 090 312
<b>HONDA</b>	08200-9017	<b>ZF</b>	TE-ML 11

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	31.9
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	6.32
Viscosity index	ASTM D2270		153
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	210
Colour	VISUAL		GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

