

# CHAMPION HYDRAULIC HLP-D ISO 46

*This is a mineral oil-based hydraulic fluid containing a selective additive system, for protection of hydraulic systems, plus the addition of detergent/dispersant additives. It meets the HLPD requirements.*

## APPLICATIONS

*This oil is suited for use in hydraulic systems, where due to high ingresses of water or contamination a high level of dispersancy is required to prevent water dropout in the system.*

## FEATURES

*Anti-wear and oxidation stability: superior protection.*

*Anti-foam properties: excellent anti-foam properties.*

*Temperature stability: adequate viscosity stability.*

## PERFORMANCE

<b>DIN</b>	51524 T2 HLPD	<b>MAN</b>	N698-H-LPD
------------	---------------	------------	------------

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.879
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	49.7
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	7.4
Viscosity index	ASTM D2270		110
Pour point	ASTM D6892	°C	-27
Flash Point COC	ASTM D92	°C	210

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

