

CHAMPION ANTIFREEZE EVO LL

High-performing coolant concentrate based on ethylene glycol with state-of-the-art PSi-OAT corrosion protection technology, for modern high performance engines. With the PSi-OAT technology, organic acids work together with mineral inhibitors for the best possible protection.

This G12 evo coolant concentrate can be used in G13, G12++, G12+, and G11 applications.

APPLICATIONS

This concentrate must be diluted with water before use. It may only be used in a concentration of at least 33 vol% to a maximum of 60 vol%. We recommend a mixing ratio of 50:50 [vol.%] with only demineralised or distilled water.

It offers long-term protection in VW TL 774 L [G12 evo] applications and many more OEM applications.

FEATURES

Total system protection: excellent heat transfer and dispersion.

Anti-corrosion properties: outstanding corrosion protection.

Antifreeze properties: superior cold temperature performance.

SPECIFICATIONS

2G	-	APRILIA	-
AFNOR	NF R 15-601	ASTON MARTIN	.
ASTM	D1384	ATLAS	-
ASTM	D3306	AUDI	-
ASTM	D4340	BMW	LC-18
ASTM	D4985	BMW	LC-87
ASTM	D6210	BMW	LC-97
AUSTRALIEN STD	AS 2108-2004	BUGATTI	-
BS	6580-2010	BYD	.
CHINESE STANDARD	GB 29743	CASE	JIC-501
CUNA	NC 956-16	CASE	MAT 3624
JIS	K2234:2018	CATERPILLAR	GCM34
KOREAN STD	KS M 2142	CHEVROLET	.
MIL	BT-PS-606 A	CHRYSLER	.
MIL	DCSEA 615/C	CITROËN	-
MIL	E/L-1415b	CLAAS	-
MIL	FS 6850-0951	CUMMINS	85T8-2
MIL	TL 6850-0038	CUMMINS	CES 14439
NATO	S759	CUMMINS	CES 14603
POLISH STANDARD	PN-C-40007	DACIA	.
SAE	J1034	DAEWOO	-
SAE	J1941	DAF	MAT 74002
SAE	J814	DAIHATSU	-
SANS	1251:2005	DAIMLER TRUCK	DTFR 29C100
SWISS FED.LAB	EMPA 170'803	DAIMLER TRUCK	DTFR 29C110
UNE	26-361-88/1	DAIMLER TRUCK	DTFR 29D120
ALFA ROMEO	.	DEUTZ	DQC-CA-14

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION
LUBRICANTS

DEUTZ	DQC-CB-14
DEUTZ	DQC-CC-14
DEUTZ-FAHR	-
DODGE	.
DUCATI	-
EICHER ENGINES	-
FAUN	-
FENDT	-
FERRARI	.
FORD	.
FORD	WSS-M97B44-D
FORD	WSS-M97B57-A1
FUSO	-
FVV STD	FVV R 530:2005
GILERA	-
GM	B 040 1065
GM	GMW 3420
GMC	.
HINO	-
HITACHI	-
HONDA	.
HUERLIMANN	-
HYUNDAI	.
IRISBUS	-
IRIZAR	-
ISUZU	.
IVECO	18-1830
JAGUAR	.
JAGUAR	CMR 8229
JAGUAR	E-VEHICLES
JAGUAR-LAND ROVER	STJLR.651.5003
JD	-
JEEP	-
JENBACHER	TA 1000-0200
KAWASAKI	-
KIA	.
KOBELCO	-
KOMATSU	-
KTM	-
KYMCO	-
LADA	.
LAMBORGHINI	-
LANCIA	.
LAND ROVER	.
LAND ROVER	E-VEHICLES
LAND ROVER	STJLR.651.5003
LEXUS	.
LIEBHERR	-
LIEBHERR	LH-00-COL5C
LOTUS	-
MAHLE	-
MAN	175D
MAN	324 NF
MAN	324 Si-OAT
MAN	324 Si-OAT EVO
MAN	324 SNF

MAZDA	.
MB	325.0
MB	325.3
MB	325.5
MB	325.6
MIL	FSD 8704
MINI	LC-87
MITSUBISHI	.
MTU	MTL 5048
MWM	-
NISSAN	-
OPEL	.
OPEL	B 040 240
OPEL	GME L1301
PERKINS	-
PIAGGIO	.
PORSCHE	-
PSA	-
RENAULT	-
ROLLS-ROYCE	.
ROLLS-ROYCE	LC-87
ROLLS-ROYCE	MTL 5048
ROVER/MG	-
SAAB	.
SAAB	690 1599
SAME	-
SCANIA	-
SCANIA	TB 1451
SEAT	.
SETRA	-
SKODA	.
SMART	.
STEYER MOTORS	-
SUBARU	.
SUZUKI	.
SYM	-
TADANO	-
TESLA	-
TGB	-
TOYOTA	.
TRIUMPH	-
VAN HOOL	-
VAUXHALL	GME L1301
VAUXHALL	GMW 3420
VOLVO	TR-31854114-002
VW	TL 774-C [G11]
VW	TL 774-D [G12]
VW	TL 774-F [G12+]
VW	TL 774-G [G12++]
VW	TL 774-J [G13]
VW	TL 774-L [G12 EVO]
YAMAHA	-
YANMAR	-

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com





TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Freezing point 50% vol. AF	ASTM D1177	°C	-36
Reserve alkalinity	ASTM D1121	ml 0.1M HCl	10.5
Density at 20°C	ASTM D4052	g/ml	1.125
Colour	VISUAL		PINK

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

