

# CHAMPION COOLANT G11 GREEN -17°C

A diluted on ethylene glycol based coolant for use in engines. It employs Inorganic Acid Technology (IAT) inhibitor and is nitrite, amine and phosphate (NAP) free and includes borate and silicate. This sophisticated technology eliminates the formation of silicate gel which is observed with inferior products. Ready to use solution.

## APPLICATIONS

Formulated for use in hot weathers in all engines including those constructed from aluminium alloys. Best choice for cooling systems that have copper/brass radiators and heater cores, especially for the lead solder used in them. Suitable for cooling circuits of the open or closed type (vehicles and heating) with a protection against freezing until -17°C.

This solution is ready to use and can be used during the whole year.

## FEATURES

Anti-freeze properties: superior cold temperature performance

Anti-corrosion properties: outstanding corrosion protection

Total system protection: excellent heat transfer and dispersion.

## SPECIFICATIONS

<b>AFNOR</b>	NF R 15-601	<b>FORD</b>	SSM-97B9102A
<b>ASTM</b>	D3306	<b>GM</b>	B 0400240
<b>ASTM</b>	D4985	<b>GME</b>	13368
<b>BS</b>	6580	<b>MAN</b>	324 NF
<b>POLISH STANDARD</b>	PN-C-40007	<b>MB</b>	325.0
<b>SAE</b>	J1034	<b>MTU</b>	MTL 5048
<b>BMW</b>	N600.69.0	<b>SAAB</b>	690 1599
<b>DAIMLER TRUCK</b>	DTFR 29C100	<b>SCANIA</b>	S28917.3
<b>DAVID BROWN</b>	DBL-7700	<b>SCANIA</b>	TB 145
<b>FIAT</b>	55523/1	<b>VW</b>	TL 774-C (G11)

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
pH	ASTM D1287		8.1
Density at 20°C	ASTM D4052	g/ml	1.054
Colour	VISUAL		GREEN
Freezing point [refracto]	ASTM D3321	°C	-17
Water content	ASTM D1123	% wt/wt	66.0

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

