

CHAMPION OEM SPECIFIC DCT FLUID

This is a lubricant based on carefully selected very high quality base oils, specifically developed for the dual clutch transmissions (DCT) of modern passenger cars. It ensures trouble-free operation of these gearboxes.

APPLICATIONS

Mainly intended for the DCT of VAG, this fluid can also be used for other 6-speed DCT transmissions, such as Chrysler Powershift, Ford Powershift, Mitsubishi TC-SST, Volvo Powershift, BMW Drivelogic 7-speed, etc.

FEATURES

Anti-wear protection: significantly extended transmission life

Extended oil life: excellent thermal and oxidation stability

Frictional properties: very smooth gear shifting, no vibration

SPECIFICATIONS

API	GL-4	FORD	WSS-M2C218-A1
BENTLEY	G 052 524-B2	FORD	WSS-M2C936-A
BMW	83220306816	GM	DEXRON DCT
BMW	83220397244	GM	FFL-4
BMW	83220440214	GREAT WALL	GW7DCT1
BMW	83222147477	GREAT WALL	GWM 7DCT450
BMW	83222148578	HONDA	MTF III
BMW	83222148579	HYUNDAI	04300-2N110 WDHO-1
BMW	83222167666	KIA	04300-2N110 WDHO-1
BMW	83222409710	KUNLUN	DCTF-7S
BMW	83222433157	MB	236.21
BMW	83225B3AC81	MB	236.22
BMW	DCTF-1	MB	236.24
BMW	DCTF-2	MB	236.25
BMW	DTF 1	MB	239.21
BMW	FFL-4	MB	239.22
BMW	MTF LT-3	MB	SLS A0019898603
BMW	MTF LT-5	MCLAREN	FFL-4
CHERY	730DHB/DHC 7DCT300	MITSUBISHI	DIAMOND QUEEN SSTF-1
CHERY	738DHA 7DCT380	NISSAN	999MP-6TRT00P
CHERY	9009011085	NISSAN	DCT FLUID
CHRYSLER	68044345EA	NISSAN	GR6
DTFR	13C130	NISSAN	GT-R R35
FERRARI	TF DCT-F3	NISSAN	LV MT-1
FIAT	9.55550-DA11	NISSAN	R35 SPECIAL
FIAT	9.55550-HE2	PORSCHE	000.043.20
FIAT	9.55550-MZ2	PORSCHE	000.043.207.29
FIAT	9.55550-MZ6	PORSCHE	000.043.207.30
FORD	F-DC	PORSCHE	000.043.210.44
FORD	WSS-M2C200-D2	PORSCHE	000.043.305.63
FORD	WSS-M2C200-D3	PORSCHE	971.094.307.02A
FORD	WSS-M2C200-E1	PORSCHE	999.917.080.00

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION
LUBRICANTS

PORSCHE	999.917.080.01	VOLVO	BOT341 #1161838
PORSCHE	999.917.546.00	VOLVO	D1
PORSCHE	TF 0870	VOLVO	D2
PSA	1618078480	VW	G 052 171
PSA	9730 A8	VW	G 052 178
PSA	9734 S2	VW	G 052 182
PSA	JWS 2271	VW	G 052 512
PUNCH	DT2	VW	G 052 513
RENAULT	7711579456	VW	G 052 524
RENAULT	7711785243	VW	G 052 527
RENAULT	BOT450 EDC 6-Speed	VW	G 052 529
RENAULT	DC4	VW	G 052 536
RENAULT	DW5	VW	G 052 726
RENAULT	DW6	VW	G 052 798
SINOPEC	DCTF-GS	VW	G 055 512
STELLANTIS	16 934 837 80	VW	G 055 524
SUZUKI	99000-22B27-036	VW	G 055 529
TOYOTA	0888581001	VW	G 055 536
TOYOTA	JWS 2271	VW	G 055 549
TOYOTA	LF	VW	G 060 726
TOYOTA	LV 75W MT	VW	G 070 726
VOLVO	1161520-7	VW	G009317
VOLVO	1161839	VW	TL 521 82
VOLVO	32240415	ZF	0671090545
VOLVO	32240419		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.853
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	35.7
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7.26
Viscosity index	ASTM D2270		173
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	202

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

