

CHAMPION E-PULSE COOLANT

This premium "Iobrid" MEG based battery coolant combines the Organic Additive Technology with mineral [silicate] corrosion inhibitors.

APPLICATIONS

This Si-OAT battery coolant is especially developed for the protection of electric and modern combustion engines cooling systems made of aluminium and aluminium alloys.

FEATURES

Anti-freeze properties: Superior cold temperature performance.

Anti-corrosion properties: Outstanding corrosion protection.

Total system protection: Excellent heat transfer and dispersion.

SPECIFICATIONS

ASTM	D3306	ASTM	D6210
ASTM	D4985	SAE	J1034

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 20°C	ASTM D4052	g/ml	1.069
Colour	VISUAL		PINK
Freezing point	ASTM D1177	°C	-36
ELECTRIC CONDUCTIVITY (25°C)	ASTM D1125	µS/cm	2300

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION
LUBRICANTS