

CHAMPION *PRO RACING* ESTER 0W-40 MS

This sustainable RRBO racing oil, fortified with ester and PAO, increases total engine protection. It contains a precisely balanced component-blended additive system with high anti-wear and friction reducing characteristics.

APPLICATIONS

This sustainable advanced engine oil is specifically developed for race engines which operate over a wide range of temperatures and rpm.

The powerful formulation covers a large part of the racing car market thanks to its high-end properties.

FEATURES

Total engine protection: performance in keeping the engine clean.

Driving style: sporty driving.

SPECIFICATIONS

| | | | |
|---------------------|-----------|----------------|--------------|
| API | SN Plus | FORD | ST-SERIES |
| API | SP | FORD | WSS-M2C937-A |
| API | SP/RC | MB | AMG-SERIES |
| ASTON MARTIN | GT3 | PORSCHE | C40 GT |
| BMW | M-SERIES | VOLVO | T-SERIES |
| FORD | RS-SERIES | | |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.852 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 83.2 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 14.5 |
| Viscosity index | ASTM D2270 | | 182 |
| Pour point | ASTM D6892 | °C | -54 |
| Colour | VISUAL | | DARK GREEN |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

