

CHAMPION **PRO RACING**

TRANS/AXLE LS 75W-140 ESTER

This is a sustainable RRBO high performance gearbox and transaxle lubricant, enriched with ester and PAO, for racing vehicles offering an excellent anti-wear and EP protection, a better resistance at high temperatures and a longer oil life time.

APPLICATIONS

This sustainable RRBO lubricant can be used in gearboxes, transaxles and differentials with or without limited slip of racing vehicles.

FEATURES

Anti-wear protection: extended component life.

Extended oil life: excellent thermal and oxidation stability.

SPECIFICATIONS

API	GL-5	MB	235.61
API	GL-6	M-SPORT	Rally3/Rally4/Rally5/R1/R2/R3
API	MT-1	NISSAN	2189E
MIL	L-2105 B	RICARDO	SFU
MIL	L-2105 C	SADEV	SFU
MIL	L-2105 D	SALISBURY	SFU
MIL	L-2105 E	SCANIA	STO 1:0
SAE	J 2360	SCANIA	STO 2:0A
ARVIN MERITOR	0-76-N	VW	G 052 539
BMW	83 22 1 470 080	X-TRAC	SFU
BMW	83 22 2 282 583	ZF	TE-ML 05A
BMW	83 22 9 407 803	ZF	TE-ML 05B
BMW	83 22 9 407 870	ZF	TE-ML 05C
BMW	MSP/A	ZF	TE-ML 07A
CHRYSLER	68218658AA	ZF	TE-ML 12D
CHRYSLER	MS 8985	ZF	TE-ML 12N
DANA	SFU	ZF	TE-ML 16F
DREXLER	SFU	ZF	TE-ML 16G
FERRARI	PAKELO GLOBAL MULTIGEAR DLS	ZF	TE-ML 19C
FORD	ESW-M2C104-A	ZF	TE-ML 21A
FORD	ESW-M2C119-A	ZF	TE-ML 21C
FORD	WSS-M2C187-A	ZF	TE-ML 21D
FORD	WSS-M2C192A+/M2C118-A		
GM	12346140		
GM	1942386		
GM	9986226		
GM	9986290		
HEWLAND	SFU		
HOLLINGER	SFU		
MACK	GO-J		

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com





TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.898
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	179
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	24.3
Viscosity index	ASTM D2270		167
Pour point	ASTM D6892	°C	-51
Colour	VISUAL		LIGHT BROWN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

