

# CHAMPION OEM SPECIFIC 0W-40 C3 SP

This is a full synthetic lubricant based on carefully selected very high quality base oils of the latest generation, with a large field of application. It offers an excellent fluidity at low temperature, which ensures instant lubrication after starting and will bring wear to a minimum. It is suitable for hybrid cars when the OEM specifications are met.

## APPLICATIONS

This engine oil is aimed and specifically formulated for usage in gasoline and diesel passenger vehicles equipped with aftertreatment systems. It can be used in a variety of OEM diesel and gasoline engines where there is a need for a 0W-40 grade low SAPS oil.

## FEATURES

Aftertreatment protection: full aftertreatment device protection.

Cold start

: excellent fluidity at low temperature.

Total engine protection: outstanding engine cleanliness and durability.

## SPECIFICATIONS

<b>ACEA</b>	C3	<b>MB</b>	229.31
<b>API</b>	approval SN Plus	<b>MB</b>	approval 229.51
<b>API</b>	approval SP	<b>MB</b>	approval 229.52
<b>API</b>	SN	<b>MCLAREN</b>	MOB 1FS
<b>BENTLEY</b>	G 052 930-2B	<b>PORSCHE</b>	A40 Level
<b>BENTLEY</b>	G 052 930-B2	<b>PORSCHE</b>	C40
<b>CHRYSLER</b>	MS 10725	<b>RENAULT</b>	RN 0700
<b>CHRYSLER</b>	MS 12633	<b>RENAULT</b>	RN 0710
<b>FIAT</b>	9.55535-S2	<b>VW</b>	511 00
<b>GM</b>	dexos2™	<b>VW</b>	G 052 579
<b>GM</b>	dexos™R	<b>VW</b>	TL 52579

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.846
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	67.9
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	13.4
Viscosity index	ASTM D2270		204
B.N. [HCL04 method]	ASTM D2896	mg KOH/g	9.4
Pour point	ASTM D6892	°C	-48

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

