

# CHAMPION OEM SPECIFIC 0W-12 MS-BXFE

This state of the art, ultra low viscosity and high fluidity oil guarantees easy cold start and significantly reduces wear, while at the same time contributing to superior fuel economy. It also provides enhanced cleanliness and advanced total protection.

## APPLICATIONS

This new generation 0W-12 engine oil exceeds the latest and stringent BMW engine oil specification, Longlife-22 FE++ or shorter LL-22 FE++.

BMW Longlife-22 FE++ engine oils are only permitted for certain BMW Group gasoline engines with and without gasoline particulate filters (GPF) from model year 2022 onwards.

[BMW part number for 1 liter is 83215B5C945, which replaces 83215A83399]

## FEATURES

**Cold start:** excellent fluidity at low temperature.

**Fuel economy:** superior fuel economy and CO<sub>2</sub> reduction.

**Total engine protection:** superior thermal and oxidation stability.

## SPECIFICATIONS

**BMW** 83215B5C945 **BMW** LONGLIFE-22 FE++

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.844
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	32.3
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	6.39
Viscosity index	ASTM D2270		154
Pour point	ASTM D6892	°C	-45
Flash Point COC	ASTM D92	°C	224

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

