This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6-speed automatic transmissions. Its particular formulation ensures a troublefree operation and smooth gear shifting.

## **APPLICATIONS**

Mainly intended for the ZF-6 speed automatic transmissions, as fitted in BMW, Jaguar and Land Rover, it is also suitable for other OEMs, who recommend this type of fluid (e.g. Audi Quattro).

## **FEATURES**

Anti-wear protection: significantly extended transmission life Frictional properties: very smooth gear shifting, no vibration Extended oil life: excellent thermal and oxidation stability

## **SPECIFICATIONS**

AML	4G4319A509/AA/S	BENTLEY	PY112995PA
BMW	83220142516	HYUNDAI	040000C90SG
MASERATI	231603	LAND ROVER	TYK500050
ZF	TE-ML 11	BMW	ATF 2
BMW	M-1375.4	BMW	83 22 2 305 396
JAGUAR	Fluid 8432	VW	G 055 005

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm²/s	31.0
Kinematic viscosity at 100°C	ASTM D445	mm²/s	6.17
Viscosity index	ASTM D2270		152
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	202
Colour	VISUAL		AMBER

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

