TECHNICAL DATA SHEET



Product Code: 7982 Sector: Motorsport Issue No: 2 Issue Date: 01/01/22

MOTORSPORT ASSEMBLY LUBRICANT

Specially developed for competition engine building.

Application

Specially formulated for competition engine and transmission builders, this high quality assembly lubricant contains solvent refined base stocks treated with high concentration of anti-wear additives. Gives any high performance engine or transmission much needed additional lubricity in the crucial on the first start up.

Use as received for assembly of mechanical components to ensure protection during initial start-up.

Typical Characteristics

Density @ 15°C, g/ml 0.919 Kinematic Viscosity @ 100°C, cSt 28.5

Features & Benefits

- Assembly lubricant has been specifically formulated to give mechanical protection during initial start-up of newly assembled components.
- Designed to be retained on the components treated during assembly and provide very high levels of anti-wear protection, especially components that are subjected to high stress levels i.e. camshafts/followers, crankshaft bearings etc.
- Unlike assembly paste type compounds, Assembly Lubricant is fully miscible and compatible with all mineral or synthetic engine oils reducing the need for an extra oil change.

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website: www.millersoils.co.uk

