



# INSTALLATION INSTRUCTIONS

## Part Number: VF1019

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

\* FREE K&N® decal To register your warranty, please see us online at [knfilters.com/register](http://knfilters.com/register). FREE K&N® decal \*

K&N® Cabin Air Filters replace your vehicle's stock cabin filter with a reusable design that cleans and freshens incoming air. They are electrostatically charged to grab and hold dust particles. K&N® cabin air filters help control odors while they help capture most mold, mildew, fungus, spores, bacteria and germs. When they get dirty they can be cleaned and reused and best of all, they come with a No-Hassle Lifetime Limited Warranty.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

When applicable, refer to owner's manual for manufacturers installation/removal instructions. The following are helpful steps when replacing/servicing cabin air filter with K&N® cabin air filter.

1. Turn the power switch off. Ensure that the charging connector is not connected.
2. Locate and remove the panel cover below the glove box by pressing on the two tabs at the top of the cover. (Fig. 1 & Fig. 2)  
**NOTE: Depending on your vehicle, you may have a footwell light that will need to be disconnected from the panel cover.**
3. With the panel cover removed locate the cabin filter housing and remove the housing door. (Fig. 3 & Fig 4)
4. Remove the cabin filter trays from housing starting with the lower tray first, then pull down the second tray after first tray has been removed. Remove any debris that might be present inside the cabin filter housing.
5. Remove the OE cabin filters from each tray. Pay close attention to not break tabs on each tray. (Fig. 7)
6. Install K&N cabin air filter into each tray. Insert one side of the filter in first, then gently press opposite side in to tray and under the tabs. (Fig. 8)
- NOTE: The K&N filter will only fit in one direction. The cut out in the filter will face down into the tray.**
7. Install the cabin filters and trays reversing steps 1-5 to complete the cabin filter installation. With the cabin filter installed, clean an area and apply the K&N Stop Decal. The decal will help notify others that this is a reusable cabin filter.




Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7




Fig. 8



Fig. 9

Please visit our website [knfilters.com](http://knfilters.com) for a complete listing of other K&N® products for your vehicle, such as oil filters, air filters, and intake kits. We recommend refreshing your K&N® Cabin Air Filter every 12 months, or 12,000 miles. Use K&N® Refresher kit pt.# 99-6000 which includes the easy to follow instructions.