

Product Specification

CO0W-20 Fully Synthetic Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
CO0W20-1	CO0W20-4	CO0W20-5	CO0W20-20	CO0W20-60	CO0W20-200

LEVELS OF QUALITY

The lubricant CO0W-20 complies with the following international specifications:

API SN; ACEA C2; ACEA A1/B1; BMW LL-14 FE+; FIAT 9.55535-DSX, GSX; ILSAC GF-5, VOLVO VCC RBSO-2AE

DESCRIPTION

CO0W-20 is a lubricant specially designed for highly stressed downsized engines with maximum power output, for extreme fuel economy characteristics and reduced CO2 emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves.

Due to its characteristics CO0W-20 is predominantly used in Euro V and euro VI engines where an ACEA A1/B1 engine oil is specified. CO0W-20 has been specially developed and approved for use in the new VOLVO VEA (Volvo Engine Architecture) engine generation. As CO0W-20 will be our basis for new engine designs good biofuel compatibility is provided.

SAE Scale		0W/20
Density at 15°C.Kg/dm3	ASTM D1298	0.840
Viscosity at 100°C.cSt	ASTM D445	8.5
Viscosity Index	ASTM D2270	155
Flammability V.A. °C	ASTM D92	200
Pour Point °C	ASTM D97	-39
S.A.	ASTM D874	0.78
T.B.N.	ASTM D2896	7.5

The above-mentioned values are indicative of production average values and are not an integral part of the specification.

TDS Comline 0W-20_REV.3 October 2021