

Product Specification

CO5W-30C4

Fully Synthetic C4 Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
CO5W30C4-1	CO5W30C4-4	CO5W30C4-5	CO5W30C4-20	CO5W30C4-60	CO5W30C4-200

LEVELS OF QUALITY

The lubricant CO5W-30C4 complies with the following international specifications:

ACEA C4; API SN, CF; BMW LL-04; MB 229.51, 226.51; RENAULT RN0720

DESCRIPTION

CO5W-30C4 is a 100% synthetic lubricant with low ash content (Low SAPS) produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations.

The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged. It is especially recommended for vehicles of Renault and Daimler groups (MB, Smart). It is recommended to always observe the oil change interval as suggested by the car manufacturer.

SAE Scale		5W/30
Density at 15°C.Kg/dm3	ASTM D1298	0.850
Viscosity at 100°C.cSt	ASTM D445	12
Viscosity Index	ASTM D2270	160
Flammability V.A.°C	ASTM D92	210
Pour Point °C	ASTM D97	-39
S.A.	ASTM D874	0.49
T.B.N.	ASTM D2896	6

The above-mentioned values are indicative of production average values and are not an integral part of the specification.

TDS Comline 5W-30C4_REV.10 October 2021